

# TC CONTROL CABLE EPR/HYPALON

## VW-1 EPR Insulation 600 Volt 90°C Hypalon\* Jacket

### 10 AWG

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0668	2FL	45	.274 x .455	127
02-0669	2 RD	45	.455	150
02-0670	3	45	.482	185
02-0671	4	60	.559	246
02-0672	5	60	.611	309
02-0673	6	60	.666	333

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0674	7	60	.666	362
02-0675	8	60	.722	406
02-0676	9	60	.776	499
02-0677	10	60	.810	539
02-0678	12	80	.896	673

### 12 AWG

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0679	2FL	45	.250 x .407	90
02-0680	2 RD	45	.407	112
02-0681	3	45	.430	144
02-0682	4	45	.471	184
02-0683	5	60	.546	233
02-0684	6	60	.594	259
02-0685	7	60	.594	286
02-0686	9	60	.689	335
02-0687	10	60	.719	363
02-0688	12	60	.758	446

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0689	15	80	.877	563
02-0690	16	80	.900	637
02-0691	19	80	.948	735
02-0692	21	80	.996	799
02-0693	24	80	1.061	891
02-0694	25	80	1.075	921
02-0695	28	80	1.125	1017
02-0696	30	80	1.167	1080
02-0697	37	80	1.262	1332

### 14 AWG

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0698	2FL	45	.230 x .367	73
02-0699	2 RD	45	.367	89
02-0700	3	45	.387	109
02-0701	4	45	.423	123
02-0702	5	45	.462	158
02-0703	6	45	.504	176
02-0704	7	45	.504	189
02-0705	8	60	.576	230
02-0706	9	60	.617	257
02-0707	10	60	.643	279

PART NUMBER	NUMBER OF CONDS.	OVERALL JACKET THICKNESS (MILS)	APPROX. OUTSIDE DIAMETER (INCHES)	APPROX. WEIGHT 1000 FT. (POUNDS)
02-0708	12	60	.677	318
02-0709	15	60	.746	415
02-0710	16	60	.766	439
02-0711	19	60	.808	545
02-0712	21	80	.890	597
02-0713	24	80	.946	668
02-0714	30	80	1.039	801
02-0715	37	80	1.122	940

\*Hypalon is a registered DuPont trademark for chlorosulfonated polyethylene (CSPE).

The data listed above is approximate and subject to normal manufacturing tolerances. Specifications are subject to change without notice.



PITTSBURGH WIRE & CABLE INC.

www.pittsburghwire.com

Sales and Ordering: 1-800-458-1222