

HOOK-UP & LEAD WIRE

1061

DESCRIPTION

Semi-rigid Polyvinylchloride (PVC) (80°C) (300 Volts) (UL) & (CSA IA/B)

Sizes

#24 AWG - #16 AWG.

Insulation

Polyvinylchloride

APPLICATIONS

Can be used for wiring of electronic equipment.

| PART NUMBER | AWG | STRANDING | NOMINAL INSULATION | NOMINAL O.D. | APPROX. LBS/K FT | UL STYLE | CSA TYPE |
|-------------|-----|--------------|--------------------|--------------|------------------|----------|----------|
| 05-0001 | 24 | 7/32 Tinned | .009 | .044 | 2 | 1061 | SR-PVC |
| 05-0003 | 22 | 7/30 Tinned | .009 | .051 | 3 | 1061 | SR-PVC |
| 05-0005 | 20 | 10/30 Tinned | .009 | .058 | 5 | 1061 | SR-PVC |
| 05-0007 | 18 | 16/30 Tinned | .009 | .068 | 6 | 1061 | SR-PVC |
| 05-0009 | 16 | 26/30 Tinned | .009 | .080 | 9 | 1061 | SR-PVC |

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

See Color Code, Chart 4, for stocked colors available.