

HOOK-UP & LEAD WIRE

1028/1283/1284/TEW (TINNED COPPER)

DESCRIPTION

Polyvinylchloride (PVC) Machine Tool Wire (MTW)/Thermoplastic Equipment Wire (TEW) (90°C MTW) (UL & CSA 105°C) (VW-1 & Moisture Resistant) (600 Volts)

Sizes

#8 AWG - #4/0 AWG.

Insulation

Polyvinylchloride

APPLICATIONS

Can be used for control cabinets, internal wiring of appliances and for machine tools.

PART NUMBER	AWG	STRANDING	NOMINAL INSULATION	NOMINAL O.D.	APPROX. LBS/K FT	UL STYLE
05-0121	8	133/29 Tinned	.048	.264	72	1028/1231/1344
05-0123	6	133/27 Tinned	.062	.326	117	1232/1283/1346
05-0125	4	420/30 Tinned	.062	.376	175	1232/1283/1346
05-0127	2	665/30 Tinned	.064	.456	263	1232/1283/1346
05-0129	1	836/30 Tinned	.085	.530	342	1232/1284/1338
05-0131	1/0	1045/30 Tinned	.082	.574	419	1232/1284/1338
05-0133	2/0	1330/30 Tinned	.082	.620	537	1232/1284/1338
05-0135	3/0	1672/30 Tinned	.085	.680	672	1232/1284/1338
05-0137	4/0	2109/30 Tinned	.082	.739	819	1232/1284/1338

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

See Color Code, Chart 4, for stocked colors available.