

HOOK-UP & LEAD WIRE

1056/1060/1275/1276

DESCRIPTION

Polyvinylchloride (PVC) Heavy Wall Lead, Hookup Wire and Refrigeration Wire (105°C) (VW-1 & Moisture Resistant) (600 Volts) (UL & CSA)

Sizes

#18 AWG - #10 AWG.

Insulation

Polyvinylchloride

APPLICATIONS

Can be used in appliances, equipment, ballasts, controls, electronic circuits, hookups, motors, panels, switchboards, transformers, electric, refrigeration equipment and room cooler units.

PART NUMBER	AWG	STRANDING	NOMINAL INSULATION	NOMINAL O.D.	APPROX. LBS/K FT	UL STYLE	CSA TYPE
05-0139	18	16/30 Bare	.060	.168	17.4	1054/1056/1235/1275	105°C TEW/AWM
05-0141	16	26/30 Bare	.060	.188	23.1	1054/1056/1235/1275	105°C TEW/AWM
05-0143	14	41/30 Bare	.075	.236	36.5	1058/1060/1322/1276	105°C TEW/AWM
05-0145	12	65/30 Bare	.075	.253	46.2	1058/1060/1322/1276	105°C TEW/AWM
05-0147	10	105/30 Bare	.075	.292	66.1	1058/1060/1322/1276	105°C TEW/AWM

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

See Color Code, Chart 4, for stocked colors available.



PITTSBURGH WIRE & CABLE INC.

www.pittsburghwire.com

Sales and Ordering: 1-800-458-1222